

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (currently amended): A fluid dispenser comprising:
  - a fluid reservoir (1; 1') provided with an opening (~~10; 10'~~), the opening being formed by a neck (10) having a top end (12) and an inside wall defining a narrow aperture segment (111) in the vicinity of the top end, and a recessed segment (112) which extends below the narrow aperture segment;
  - a dispensing member (2) provided with a body; and
  - a fixing member (3; 3') for fixing said body in the opening;said fixing member being provided with a skirt (31; 31') serving to come into engagement in the opening, and with a sleeve (32) serving to come into engagement around the body;
- said fluid dispenser being characterized in that the body forms a cam segment (204) for deforming the skirt outwards into pressed contact with the opening, the skirt (31) having a sealing zone (313) which, in the final position, comes into leaktight contact with the narrow aperture segment (111), and a fixing zone (314) which, in the final position, comes into tight-fitting contact with the recessed segment (112).

2. (Original): A fluid dispenser according to claim 1, in which the body (20) has a large-diameter segment (207) on which the sleeve (32) comes into leaktight engagement in the final assembled position.

3. (currently amended): A fluid dispenser according to claim 1, in which the body (20) has an intermediate segment (205) situated above the cam segment (204) and below the large-diameter segment (207), the skirt (31; 31') coming into tight-fitting engagement with said intermediate segment (205) ~~(20)~~; in the final assembled position, the sleeve (32) being in engagement with said intermediate segment (205) before the skirt comes into engagement with the cam segment (204).

4. (Original): A fluid dispenser according to claim 3, in which the body (20) has a small-diameter segment (203) situated below the cam segment (204), the skirt (31; 31') being in engagement with the small-diameter segment (203) when the sleeve (32) is in engagement with the intermediate segment (205) .

5. (Original): A fluid dispenser according to claim 1, in which the opening has a substantially cylindrical inside wall.

6. (Original): A fluid dispenser according to claim 1, in which the skirt forms tabs (314) separated by slots (315).

7. (Original): A fluid dispenser according to claim 1, in which the body (20) forms a top collar (208) under which the sleeve (32) comes into abutment in the final position.

8. (Original): A fluid dispenser according to claim 3, in which the sleeve (32) has an inside wall that forms a holding bead (321) adapted to come into tight-fitting engagement with the intermediate segment (205) to hold the fixing member (3) in place on the body (20) when it is inserted into the neck.

9. (Original): A fluid dispenser according to claim 1, in which the skirt (31) has an inside wall provided with a cam bead (311) serving to come into engagement with the cam segment (204) .

10. (currently amended): A fluid dispenser according to claim 1 i, in which the skirt (31; 31') is provided with a bottom lip (316) in contact with the body (20).

11. (Previously Presented): A fluid dispenser according to claim 9, in which the skirt (31; 31') is in contact with the intermediate segment (205) via the cam bead (311) and via the bottom lip (316) only.

12. (Original): A fluid dispenser according to claim 1, in which the fixing member (3) is provided with an abutment flange (33) serving to come freely into contact with the opening (10; 10') without being force-fitted.

13. (canceled).

14. (Previously Presented): A fluid dispenser according to claim 10, in which the skirt (31; 31') is in contact with the intermediate segment (205) via the cam bead (311) and via the bottom lip (316) only.

15. (new): A fluid dispenser comprising:

a fluid reservoir having an opening formed by a neck, the neck having a top end and an inside wall defining a narrow aperture segment in the vicinity of the top end, and a recessed segment which extends below the narrow aperture segment;

a dispensing member comprising a body; and

a fixing member that secures the body in the opening;

the fixing member comprising a skirt that engages come into engagement the opening from within and a sleeve that engages around the body;

wherein the body comprises a cam that deforms the skirt outwards into pressed contact with the opening prior to final positioning of the dispenser within the opening, the skirt comprising a sealing zone that, in a final position of the skirt, is in leaktight contact with the

*Amendment Under 37 C.F.R. § 1.111*  
*U.S. Application No. 10/677,342*

*Attorney Docket No.: Q73141*

narrow aperture segment, and a fixing zone that, in the final position of the skirt, is in tight-fitting contact with the recessed segment.